

OmniLink® TM-H6000VI

Multifunction POS Printer
with Check Processing



Multifunction hybrid POS receipt printer with check processing.

Fastest multifunction hybrid printer in the industry¹ — up to 500 mm/sec² for faster transaction times

Accurate check processing — robust slip and endorsement printing; MICR accuracy of 99.9 percent

Engineered for reliability — long-life printhead and auto cutter³; easy-to-clean, water-resistant enclosure; backed by 2-year limited warranty

Advanced paper-saving functions — help reduce costs with up to 49 percent reduction in paper usage⁴

Real-time remote monitoring⁵ and management — get remote access to the printer's status, maintenance counters, part life expectancy and settings

Multiplatform support — compatible with traditional POS terminals and mobile devices

Online ordering capability — Server Direct Print function allows the printer to retrieve orders from a Web server and print a receipt without requiring integration with POS software

Flexible setup and configuration — Epson TM Utility app⁶ streamlines the setup process; additional memory enables multilingual support on each printer

POS peripheral support — supports POS peripherals such as payment terminals and customer displays

Print

Printing Method

Receipt: Thermal line
Slip, Endorsement: 9-Pin serial impact dot matrix

Print Speed

Receipt: Up to 500 mm/s
Slip: Up to 5.7 ips
Endorsement: Up to 4.0 ips

Print Resolution

Receipt: 180 dpi

Print Fonts

Thermal Print Fonts (Name, Structure [W x H dots], Size [mm], Horizontal Dot Spacing, Columns Per Line [cpl])

ANK Font A, 12 x 24 dots, 1.41 mm x 3.39 mm, 2 dots, 42 cpl
ANK Font A (46 column emulation), 11 x 24 dots, 1.27 mm x 3.39 mm, 1 dot, 46 cpl

ANK Font B, 9 x 17 dots, 0.99 mm x 2.40 mm, 2 dots, 56 cpl

ANK Font C, 10 x 20 dots, 1.27 mm x 2.82 mm, 1 dot, 36 cpl

Multi-Byte Font, 24 x 24 dots, 3.39 mm x 3.39 mm, 0 dots, 15 cpl

Slip Print Fonts (Name, Structure [W x H dots], Size [mm], Horizontal Dot Spacing, Columns Per Line [cpl])

ANK Font A, 5 x 9 dots, 1.56 mm x 3.11 mm, 1 dot, 45 cpl

ANK Font B, 7 x 9 dots, 1.24 mm x 3.11 mm, 2 half-dots, 60 cpl

Multi-Byte Font, 16 x 16 dots, 2.67 mm x 2.94 mm, 2 dots, 30 cpl

Endorsement Print Fonts (Name, Structure [W x H dots], Size [mm], Horizontal Dot Spacing, Columns Per Line [cpl])

Endorsement Font, 5 x 7 dots, 1.09 mm x 2.41 mm, 1 dot, 40 cpl

ANK Font A, 5 x 9 dots, 1.56 mm x 3.11 mm, 1 dot, 25 cpl

ANK Font B, 7 x 9 dots, 1.24 mm x 3.11 mm, 2 half-dots, 33 cpl

Character Sets

95 alphanumeric characters, 18 international sets, 128 x 43 graphic, Simplified Chinese (GB18030-2022 or GB2312), Traditional Chinese (Big5)

Barcode Printing (Receipt and Slip)

UPC-A, UPC-E, JAN 8/EAN 8, JAN 13/EAN 13, Code 39, Code 93, Code 128, Code 128 Auto, ITF, CODABAR(NW-7), GS1-128, GS1 DataBar (Truncated, Limited, Expanded)

Two-Dimensional Symbol (Receipt)

PDF417, Max Code, Data Matrix, Aztec Code, Two-Dimensional GS1 DataBar, Composite Symbology

Media Handling

Media Dimensions

Receipt: 79.5 ± 0.5 mm (width) x 83 mm (roll diameter)
Slip: 68 – 230 mm (width) x 68 – 297 mm (height); 68 mm x 152 mm minimum size

Thickness

Receipt: 48 – 80 µm

Slip/Endorsement: 0.09 – 0.22 mm single-ply

Copy Capacity

Slip: One (1) original and three (3) copies
Endorsement: One (1) original and two (2) copies

Inked Ribbons and Life

Slip: ERC-32B; up to 4,000,000 characters
Endorsement: ERC-43B; up to 3,000,000 characters

Connectivity

Interfaces (Built-In Plus Choice of Connect-It™ Interface)

Built-in: USB Type-B, Ethernet (10/100Base-T/TX), USB Type-A peripheral device port

Connect-It Interfaces (UIB): Serial, Parallel, Powered USB, Wireless

Communication Protocols ESC/POS®, ePOS-Print Service (Ethernet/Wireless), Server Direct Print (Ethernet/Wireless)

Easy Setting Function NFC, QR Code

Easy Setting Tool TM-H6000VI Utility (Windows®), EpsonNet Config

General

Data Buffer

Receive: 45 bytes or 4KB, selectable

User-defined: 12KB

Macro buffer: 2KB

NV Graphics: 384KB (maximum)

NV User: 1KB (maximum)

Development Kit OPOS ADK (Windows), JavaPOS ADK (Windows, Linux®), OPOS ADK for .NET (Windows)

Drivers Epson Advanced Printer Driver (APD), TM Virtual Port Driver, Linux Printer Driver

Software TM-H6000VI Utility (Windows), EpsonNET Config, Deployment Tool, Monitoring Tool, TM-H6000VI Firmware Updater, BmpToRaster Slip Paper Sensor Adjustment Tool (Windows)

LED Indicators Power, Error (1, 2, 3), Paper, Slip

Sensors Paper-End, Near-End, Cover Open, Slip Paper Sensor

D.K.D. Function Yes (2 drivers)

Average Power Consumption Operating: 26.6 W, Standby: 1.0 W

Power Supply Adapter PS-190 (Included on Select SKUs)

Power Source 24 VDC ± 7%

Dimensions (W x D x H) 7.32" x 10.95" x 7.13"

(186 mm x 278 mm x 181 mm)

Weight Approx. 9.7 lb (4.4 kg)

Case Color Black (EBCK), White (ENN8.5)

Standards and Approvals EMI FCC Class A, ICES-3 (A)/NMB-3 (A), cTUVus

USB POS Peripheral Device Support 1

Eco Features

Power-Saving Mode

ENERGY STAR® qualified (select SKUs)

RoHS compliant

End-of-life options available⁷

Epson America, Inc. is a SmartWay® Transport Partner⁸

What's Included

OmniLink TM-H6000VI, Thermal Roll Paper (starter roll for testing), Setup Guide, Power Switch and Connector Covers, ERC-32(B) Ribbon Cassette, ERC-43(B) Ribbon Cassette (endorsement models only), AC Adapter and AC Cord (Contents vary by individual SKU, including AC adapter and cord.)

Warranty

2-year limited in the U.S. and Canada; optional extended service plans available

Epson PreferredSM Plus Extended Service Plans⁹

1-Year Return for Repair	EPPSDEXTB1
2-Year Return for Repair	EPPSDEXTB2
3-Year Return for Repair	EPPSDEXTB3
1-Year Spare-in-the-Air Coverage	EPPSDSITAB1
2-Year Spare-in-the-Air Coverage	EPPSDSITAB2
3-Year Spare-in-the-Air Coverage	EPPSDSITAB3
4-Year Spare-in-the-Air Coverage	EPPSDSITAB4
5-Year Spare-in-the-Air Coverage	EPPSDSITAB5

Ordering Information

Model	Interface*	Power Supply	Color	Part Number
Endorsement Model				
OmniLink TM-H6000VI	Serial	Yes	EBCK	C31CL25032
OmniLink TM-H6000VI	Serial	No	EBCK	C31CL25034
OmniLink TM-H6000VI	Powered USB	No	EBCK	C31CL25036
OmniLink TM-H6000VI	Parallel	Yes	EBCK	C31CL25A9981
OmniLink TM-H6000VI	Serial	Yes	ENN8.5	C31CL25031
OmniLink TM-H6000VI	Powered USB	No	ENN8.5	C31CL25A9951
Validation Model				
OmniLink TM-H6000VI	Serial	No	EBCK	C31CL25054
Accessories				
Color Customer Display Black (DM-D70)				A61CH62111
Color Customer Display White (DM-D70)				A61CH62101
Customer Display Black (DM-D30)				A61CF26111
Customer Display White (DM-D30)				A61CF26101
Wireless USB Adapter (OT-WL06)				C32C891321
Proximity Beacon Adapter (BT-820)				C32C824A8761

* All models have built-in USB and Ethernet interfaces.

For additional options, please contact your Epson representative.

WARNING: The paper roll shipped together with this product can expose you to chemicals, including Bisphenol A and Bisphenol S, which are known to the State of California to cause birth defects or other reproductive harm. **Wash hands after handling.**

For more information, go to www.P65Warnings.ca.gov

1 Compared to multifunction hybrid thermal receipt printers available in the U.S. as of January 2024, based on manufacturers' published specifications. | 2 Speed based on using 80 mm wide media only and Epson's PS-190 power supply. Configurations not including the PS-190 will have a default print speed of 450 mm/sec. | 3 Rated printhead and cutter lives based on use of the following media only, with printer operated at room temperature and normal humidity: Model KT55FA: Papierfabrik August Koehler SE, Model PD160R: Oji Imaging Media Co. Ltd., Model TF50KS-Y: NIPPON Paper Industries Co. Ltd. | 4 Paper savings depend on the text and graphics printed on the receipt. | 5 Requires customization with third-party applications. | 6 Download and compatible device required. Data usage fees may apply. See User's Guide for details. | 7 For convenient and reasonable recycling options, visit epson.com/recycle | 8 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. | 9 Product comes with 2-year limited warranty with the option to purchase extended service plans up to a total of 5 years of continuous coverage. Extended service plan must be purchased within 90 days of product purchase. See individual service plan for details.

See the latest innovations from Epson Business Solutions at epson.com/forbusiness



Epson America, Inc.
3131 Katella Ave., Los Alamitos, CA 90720

Epson Canada Limited
185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.ca

Specifications and terms are subject to change without notice. EPSON and ESC/POS are registered trademarks of Seiko Epson Corporation. OmniLink is a registered trademark and Connect-It and Epson Preferred are trademarks of Epson America, Inc. Windows is a trademark of the Microsoft group of companies. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2025 Epson America, Inc. CPD-64253R4 4/25

Contact: